

STSK4750B

\\BACK UP CAMERA SYSTEMS

7" MIRROR/MONITOR Backup Camera System


VEHICLE TYPES





Rosco's new 7" mirror/monitor kit includes the STSM244SC that can easily be mounted on the vehicle's existing rear view mirror button. This new addition to the MOR -Vision® product line allows 1 camera input and includes a 50' extension harness.







INTUITIVE USER INTERFACE

COMPATIBILITY

KIT COMPONENTS: MONITOR: STSM244SC

CAMERA: STSC130BC0 HARNESSES: STSH130 (ADAPTER HARNESS) STSH349 (50' EXTENSION HARNESS)

STSM244SC MONITOR	FEATURES	STSM244SC MONITOR	FEATURES
SCREEN SIZE	7"	VIEWING ANGLES	L/75°, R/75°, UP/60°, DOWN/60°
RESOLUTION	800 x 480 pixels	SHOCK RATING	2G
BRIGHTNESS BEFORE MIRROR GLASS	1000 cd/m2	VIBRATION RATING	6G
BRIGHTNESS AFTER MIRROR GLASS	700cd/m2	POWER SUPPLY	12 ~ 32 VDC
NUMBER OF CAMERA INPUTS	1	OPERATING TEMPERATURE RANGE	-4°F to 158°F -20°C to 70°C
INPUT FORMAT	4-pin	STORAGE TEMPERATURE RANGE	-22°F to 176°F -30°C to 80°C
NUMBER OF TRIGGER INPUTS	1	MAXIMUM CURRENT CONSUMPTION	1,000mA

1-800-227-2095





STSK4750B

\\BACK UP CAMERA SYSTEMS

BACKUP CAMERA

VEHICLE TYPES





The STSC130BCO is a mini backup color camera with a 150° field-of-view to capture a wide vlew for drivers when in reverse. This versatile camera is also available in white and chrome.





STSC130BCO

STSC130 CAMERA	FEATURES	STSC130 CAMERA	FEATURES
RESOLUTION	733 x 493 PIXELS	FIELD OF VIEW	150°
INFRARED LED	0	INPUT VOLTAGE RANGE	DC 12V ± 2V
NIGHT VISION RANGE	N/A	OPERATING TEMPERATURE	-22°F to 149°F (-30°C to 65°C)
ILLUMINATION	0.2 LUX	WEIGHT	0.71 lbs. (0.32 kg.)
IP RATING	IP69K	DIMENSIONS W X H X D	1.5" x 1.0" x 1.4" (37mm x 25mm x 35mm)
VIBRATION RATING	10G	MICROPHONE	N/A

CAT NO 01082020

1-800-227-2095

