

SAFE-T-SCOPE®





HEAR AND SEE WHAT'S BEHIND A VEHICLE, EVEN IN THE DARK.

- High Resolution 5" LCD Color Monitor With Ultra Sharp Digital Display
- System Can Accept Up to 2 Camera Inputs for Multiple Camera Views
- + Weatherproof, Heavy Duty Camera Provides 150° Field Of Vision
- 17 High Power InfraRed LEDs in Camera Provide Up To 15 Ft. of Low Light Visibility
- Built-In Camera Mic & Powerful Monitor Speakers
- + Versatile Mounting On Dashboard or Overhead Location
- + Two Year Warranty Included







SAFE-T-SCOPE®



MONITOR P/N: STSM208









- + Optional U-Bracket STSU1004 (not included)
- + Duckfoot Mount & Sunshade Included

Screen Size Diagonal	5"		
Maximum No. of Cameras	2		
Screen Ratio	16:9		
Resolution (Pixels)	800(H) x 480(V		
Contrast Ratio	500:1		
Brightness	400 cd/m2		
Video System	NTSC		
Input Voltage Range	DC 12V to 32V		
Operating Temperature	-5°F to 149°F (-15°C to 65°C)		
Shock Rating	8G		
Vibration Rating	6.9G @ 10-30Hz, 3mm Amplitude		
Audio	Included		
Weight	0.7 lbs. (0.32 kg.)		
Dimensions W x H x D	5.5" x 4" x 1.1" (140mm x 102mm x 28mm)		
Other Features	Auto dimming backlit buttons		

CAMERA P/N: STSC101A



- + Built-in microphone for a live audio feed
- + Eighteen infrared LEDs that

Pixels	976(H) x 496 (V)	
InfraRed LEDs	17	
Night Vision Range	15 Feet (3m)	
Illumination	0 Lux (with IR LEDs)	
IP Rating	IP69K	
Shock Rating	50G @ 11ms	
Vibration Rating	2.0G @ 10Hz to 1000hz	
Field of View	150°	
Input Voltage Range	DC 9V ~ 18V	
Operating Temperature	-40°F to 185°F (-40°C to 85°C)	
Weight	0.71 lbs. (0.31 kg.)	
Dimensions W x H x D	2.75" x 1.65" x 2.12"	
Microphone	Built-in	









HARNESS P/N: STSH301 Included in STSK5065 // STSH303 Included in STSK5033



STSH301 65' Harness (included in kit)

OPTIONAL HARNESSES

+ Commercial grade 65 ft harness with (4-PIN) twist lock connectors	STSH303	33' Harness	
	STSH304	16.5' Harness Extension	
	STSH430	Heavy Duty Coil Cord Quick Disconnect Kit w/ 2 Camera Connections	

