



Color Backup Camera System With 5" LCD Monitor & Two Camera Inputs for Work Trucks, Vans, Buses, RVs & Trailers



- Rugged High Resolution 5" LCD Color Monitor
- System Can Accept Up to 2 Camera Inputs for Multiple Camera Views
- Weatherproof Heavy Duty Camera Provides 150° Field Of Vision
- Windshield Mounted with Removal of Rearview Mirror
- One Year Warranty Included

MONITOR P/N: STSM243 (Included In Kit)

Screen Size Diagonal	5"
Maximum No. of Cameras	2
Screen Ratio	16:9
Resolution (Pixels)	480(H) x 272(V)
Contrast Ratio	250:1
Brightness	350 cd/m ²
Video System	NTSC
Input Voltage Range	DC 12V to 24V
Operating Temperature	-4°F to 149°F (-20°C to 65°C)
Shock Rating	100G
Vibration Rating	2G @ 10Hz to 150Hz
Audio	Not Available
Weight	0.59 lbs. (0.27 kg.)
Dimensions W x H x D	5.0" x 3.3" x 1.0" (126mm x .84mm x 24mm)
Mounting Options	Windshield mount, Universal pod mount



CAMERA P/N: STSC130 (Included In Kit)

Pixels	480,000
Resolution Horizontal	420 TVL
InfraRed LEDs	0
Night Vision Range	16 Feet
Illumination	0.2 Lux
IP Rating	IP69K
Shock Rating	51G
Vibration Rating	10G
Field of View	150°
Input Voltage Range	DC 12V ± 2V
Operating Temperature	-22°F to 149°F (-30°C to 65°C)
Weight	0.71 lbs. (0.32 kg.)
Dimensions W x H x D	1.5" x 1.0" x 1.4" (37mm x 25mm x 35mm)
Microphone	Not Available



STSC130B STSC130W STSC130R

Optional Cameras:



STSC141
Standard Camera



STSC112
License Plate Camera



STSC106
Wide Angle Bullet Camera

HARNESS P/N: STSH343 (Included In Kit)

33' Heavy Duty w/ Twist - Lock Connectors



STSH343
Standard Harness



STSH130
Adapter Harness