

Heated Backup Camera System With Color 7" WATERPROOF Multi-View LCD Monitor

for Indoor & Outdoor Forklifts









- 7" Waterproof Monitor With Membrane Touchpad
- High Resolution With Ultra Sharp DIGITAL Display & LED-Backlit Panel
- Multi-View LCD Monitor Can Accept Up To 4 Camera Inputs
- Heavy Duty, Heated Camera Provides 114° Field Of Vision
- 6 InfraRed LEDs in Camera Provide Up To 30 Ft. of Night Time Visibility
- Integrated Audio Built-In Camera Mic & Powerful Monitor Speakers
- Versatile Monitor & Camera Mounting Options Designed For Forklifts





MULTI-VIEW WATERPROOF MONITOR P/N: STSM207 (Included In Kit)

Screen Size Diagonal Maximum No. of Cameras Screen Ratio 16:9

Resolution (Pixels) $800(H) \times 400(V)$

Contrast Ratio 300:1 400 cd/m² **Brightness** Video System **NTSC**

Input Voltage Range DC 12V to 24V

Operating Temperature -22°F to 158°F (-30°C to 70°C)


Shock Rating 100G Vibration Rating 15G Audio Included Weight 1.7 lbs. (0.78 kg.)

Mounting Options

Dimensions W x H x D 7" x 5.75" x 1" (181mm x 134mm x 28mm)

Other Features Sunshade, IP67 Water & Dust Rating

U-Bracket with Specialized / Universal Forklift Mounting Plate





HEATED CAMERA P/N: STSC107 (Included In Kit)

Pixels 250,000 Resolution Horizontal 380 TVL InfraRed LEDs 6 High Output Night Vision Range 30 Feet

Illumination 0 Lux (with IR LEDs)

IP Rating IP67 **Shock Rating** 100G Vibration Rating 15G Field of View 114°

Input Voltage Range DC 12V \pm 2V

Operating Temperature -22°F to 158°F (-30°C to 70°C)

Weight 0.8 lbs. (0.4 kg.) Dimensions W x H x D 2.7" x 1.7" x 2.2"

(70mm x 44mm x 57mm)

Microphone Included

Other Features Thermostat Controlled Heater,

Auto Light Sensor

Comes Complete w/ Universal Camera Mounting Options

Forklift Mounting Bracket



STSC107 Standard Camera



STSC127 Shutter Camera



Optional Cameras:



STSC128 Side Mount Camera

HARNESS P/N: STSH308 (Included In Kit)

16.5' Harness

Optional Harnesses:

STSH307 - 60' Harness

STSH310 - 60' Harness Extension (used with STSH308)

STSH306 - 60' Harness (for STSC117 Only)



Standard Harness

Optional Harnesses:



STSH307



STSH310





