



STSK7360

## Heated Backup Camera With 7" Waterproof Multi-View LCD Monitor for Open & Harsh Cab Environments



KIT P/N: STSK7360

- 7" Waterproof Monitor With Membrane Touchpad
- High Resolution With Ultra Sharp DIGITAL Display & LED-Backlit Panel
- Multi-View LCD Monitor Can Accept Up To 4 Camera Inputs
- Heavy Duty, Heated Camera Provides 114° Field Of Vision
- 6 InfraRed LEDs in Camera Provide Up To 30 Ft. of Night Time Visibility
- Integrated Audio Built-In Camera Mic & Powerful Monitor Speakers
- Versatile Mounting On Dashboard or Overhead Location
- Two Year Warranty Included

### MULTI-VIEW WATERPROOF MONITOR P/N: STSM207 (Included In Kit)

Screen Size Diagonal	7"
Maximum No. of Cameras	4
Screen Ratio	16:9
Resolution (Pixels)	800(H) x 400(V)
Contrast Ratio	300:1
Brightness	400 cd/m <sup>2</sup>
Video System	NTSC
Input Voltage Range	DC 12V to 24V
Operating Temperature	-22°F to 158°F (-30°C to 70°C)
Shock Rating	100G
Vibration Rating	15G
Audio	Included
Weight	1.7 lbs. (0.78 kg.)
Dimensions W x H x D	7" x 5.75" x 1" (181mm x 134mm x 28mm)
Other Features	Sunshade, IP67 Water & Dust Rating
Mounting Options	U-Bracket with Standard Duckfoot

Overhead U-Bracket  
Mounting Option



### HEATED CAMERA P/N: STSC107 (Included In Kit)

Pixels	250,000
Resolution Horizontal	380 TVL
InfraRed LEDs	6 High Output
Night Vision Range	30 Feet
Illumination	0 Lux (with IR LEDs)
IP Rating	IP67
Shock Rating	100G
Vibration Rating	15G
Field of View	114°
Input Voltage Range	DC 12V ± 2V
Operating Temperature	-22°F to 158°F (-30°C to 70°C)
Weight	0.8 lbs. (0.4 kg.)
Dimensions W x H x D	2.8" x 1.7" x 2.2" (70mm x 44mm x 57mm)
Microphone	Included
Other Features	Thermostat Controlled Heater, Auto Light Sensor



STSC107  
Standard Camera

Optional Cameras:



STSC117  
Vertical Tilt Camera



STSC127  
Shutter Camera



STSC128  
Side Mount Camera

### HARNESS P/N: STSH307 (Included In Kit)

60' Heavy Duty w/ Twist - Lock Connectors



STSH307  
Standard Harness

Optional Harnesses:



STSH308



STSH310



STSH306

### Optional Harnesses:

STSH308 - 16.5' Harness

STSH310 - 60' Harness Extension (used with STSH308)

STSH306 - 60' Harness (for STSC117 Only)