



SAFE-T-SCOPE[®]

REARVIEW BACKUP CAMERA SYSTEMS



STSK7965

INSTALLATION / USER'S MANUAL

TABLE OF CONTENTS

STSK7965 Safe-T-Scope® 2
 Components List and description 3
 Camera Installation 4
 Monitor Installation 5
 Wiring Diagram 6-7
 Functions 8
 System Technical Descriptions 9
 How To Set Your Monitor To Your Requirements 10

STSK7965 SAFE-T-SCOPE® 7" COLOR BACKUP CAMERA SYSTEM

Rosco Vision Systems introduces a revolutionary new backup camera system for commercial vehicles. The STSK7965 Safe-T-Scope® backup camera system utilizes a 7" inch monitor to display a 16:9 LCD screen when the vehicle shifts into reverse. This monitor allows the driver to see obstructions behind the vehicle for added convenience and safety.

The camera has an advanced CCD image sensor able to process excellent views under dark and light conditions. A 120° diagonal field of vision yields superb coverage behind the vehicle, and complies with the latest U.S. DOT guidelines when installed properly.

COMPONENT LIST AND DESCRIPTION

PART NO.

DESCRIPTION

STSM251



7" MONITOR KIT



INCLUDES: STSK5465/PHAR POWER HARNESS MONITOR SUN SHIELD DUCK FOOT MOUNT

STSC141



120° REARVIEW CAMERA

STSH341



4 PIN 65FT. EXTENSION CABLE
 ADDITIONAL CABLE LENGTHS AVAILABLE

STSU1002






U-BRACKET (OPTIONAL)

CAMERA INSTALLATION

- Select a high and centered location at the rear of the vehicle to mount the STSC141 camera

IMPORTANT

- When mounting your new backup camera, it is highly recommended that the image transmitted by the camera show the rear bumper and area behind the vehicle.
- We do not recommend mounting the camera near the lower area of the vehicle (ex. bumper). This reduces the view of the camera and increases the chance of physical damage to the camera.
- Once the location for the camera is chosen, using a 3/16 drill bit, drill four holes into the vehicle using the bracket as a guide. Be sure to clear any obstacles before drilling holes.
- Using a 5/8 drill bit, drill a hole into the vehicle. Insert wire gramment and safely pass the camera wire through and mount securely in place.
- To finalize the camera installation, hand tighten the camera wire to your extension cable. Make sure male pins are inserted into female adaptor correctly. You are ready to conceal your extension cable.



MONITOR INSTALLATION

- Connect the red wire to an ignition switched accessory (ex. radio) power source, and connect the black wire to chassis ground. See wiring diagram for connections.
- Attach monitor inside vehicle in a location convenient to the driver (ex. center of dash, overhead, or flush-mounted in dash).
- Attach the "duckfoot" bracket to the dashboard or to the headline using self-tapping screws and/or adhesive pad.
- Fasten monitor to "duckfoot" and adjust mounting angle to allow optimum driver viewing comfort.
- The monitor terminates in a 13-pin connector, which should be connected to the mating 13-pin receptacle end of the power/video/audio distribution harness.
- Connect the camera extension cable from the rear-view camera to the power/video/audio distribution wire connector. The camera to cable connection is waterproof. Be sure to position the cable properly. The male end attaches to the camera. The female end attaches to the power/video/ audio distribution harness, typically located under the dashboard.
- The green wire is the REVERSE trigger wire. In typical rear-view installations, connecting this wire to the vehicle's backup light circuit will activate the rear-view image whenever the vehicle shifts into reverse.
- Feed as much cable as possible into vehicle and clamp securely. This reduces the possibility of it being hooked or snagged.
- Keep all cables away from HOT, ROTATING and ELECTRICALLY NOISY components.
- FUEL TANKERS & OTHER SPECIALTY VEHICLES: All electrical equipment fitted to petroleum vehicles must be connected via battery master switch and must be isolated from the battery while the vehicles are loading and unloading. For other specialty vehicles, please check applicable code and regulations prior to installation.
- Always consult your dealer when fitting any electrical or electronic equipment to a vehicle fitted with a CAN-bus multiplex system.

STSK7965

Wiring Diagram

STSM251




13 Pin Connector



STSK5465/PHAR

Power Distribution Harness



Green wire is the reverse trigger wire, connect to vehicle backup light circuit. Monitor will turn on when the vehicle shifts into reverse

GREEN (REVERSE TRIGGER, CAM 1)

WHITE (OPTIONAL CAM 2 TRIGGER) White wire is an optional 2nd 12V trigger for use only if CAM 2 is connected

POWER 12 VDC

Connect the red wire 12Vdc to an ignition switched accessory (ex. radio) power source

Filter/Fuse

GROUND

OPTIONAL SECOND CAMERA (NOT INCLUDED IN KIT)

STSC109



F

M

C2

(optional second camera)

STSC118



F

REVERSE CAMERA



STSC141

4 Pin Connector

4 Pin Connector

STSH341(65FT)

Camera Cable

4 Pin Connector

4 Pin Connector

C1

FUNCTIONS AND OPERATION

MONITOR

• POWER

When the ignition is switched on, the monitor will be in standby mode (a steady red light will indicate that the monitor is energized, no image will appear on the screen until triggered or manually turned on. The trigger wire is energized by 12VDC power from a backup light or circuit. A steady green light will appear on your monitor. The image captured by the selected camera will appear on the monitor.

- Pressing the power switch will change the monitor status from standby to steady-on. Steady-on mode status will show camera view depending on user selection

• VOLUME +/-

Adjust Speaker Volume

These buttons are also used to adjust the values within selected setting of menu option

• 'MENU' BUTTON (See p. 9)

Press the MENU button to open on screen options.

Press Menu to cycle through choices and +/- to change your settings

• C1/C2 (NOT APPLICABLE FOR STSK7465)

Switched from Camera 1 to Camera 2 and vice-versa

SYSTEM TECHNICAL SPECIFICATIONS:

STSM251: (Includes STSK5465/PHAR, BAS4515, STSDF1000)

Screen size (diagonal):	7"
Maximum No. of cameras:	2 Inputs/Channels
Screen ratio:	16:9
Contrast ratio:	500:1
Video system:	NTSC
Voltage input:	12 ~32 Vdc
Operating temperature °F (°C):	5° to 149° (-15° to +65°)
Storage temperature:	-4° to +158° (-20° to + 70°)
Shock rating:	100g
Vibration Rating:	6g
Speaker Impedance:	8 Ohms
Weight:	0.9 Lb.
Dimensions W x H x D:	5.7" x 4.9" x 1"

STSC141: (Includes Sunshade and Mounting Hardware)

Image device:	Sony ¼" CCD
Pixels:	270,000
TV lines:	420
InfraRed LED's:	18 High-Output
Minimum illumination:	0 Lux (infrared LED's on)
Night vision range:	30 feet
Video Output:	1.0 Vp-p, 75 Ohm
Shock rating:	100G
Vibration rating:	15G
Field of view:	120°
Operating temperature °F (°C):	-4° to +140° (-20° to + 60°)
Storage temperature °F (°C):	-40° to +176° (-40° to + 80°)
Weight:	.6 lb.
Dimensions W x H x D:	3" x 2" x 2"

STSH341: (Included in Kit)

65' Heavy Duty w/ Twist - Lock Connectors

WIRING NOTES

- Please read this manual carefully before using the product.
- This system is intended as an aid to safe reverse operation.
- Drivers must always use extreme caution when operating a vehicle.
- Specifications subject to change without prior notice.
- Keep all cables AWAY from rotating and electrically noisy components.
- Make sure all cables are fastened properly so that you can prevent wire chafing, kinks, cuts, etc...
- Always consult your dealer when fitting any electrical or electronic equipment to a vehicle fitted with a CAN-bus or multiple system.



WARNING

- To prevent electrical shock, DO NOT OPEN MONITOR CASE.
- Avoid exposing monitor to water, rain, moisture etc.
- Do not disassemble the camera. This voids the warranty.
- Disassembling the camera will compromise the waterproof seal.

HOW TO SET UP YOUR SYSTEM REQUIREMENTS



NOTE

- No changes can be made to the monitor while the vehicle is in reverse.
Never change settings while the vehicle is in operation.
- Press the MENU button once to set desired brightness. Press +/- to increase/reduce the brightness.
Wait 3 seconds to exit setup mode.
- Press the MENU button twice to set desired contrast. Press +/- to increase/reduce the contrast.
Wait 3 seconds to exit setup mode.
- Press the MENU button three times to set desired color. Press +/- to increase/reduce the color.
Wait 3 seconds to exit setup mode.
- Press the MENU button four times to set desired tint. Press +/- to increase/reduce the tint.
Wait 3 seconds to exit setup mode.
- Press the MENU button five times to set desired language. Press +/- to select English/French/Spanish.
Wait 3 seconds to exit setup mode.
- Press the MENU button six times to reset. Press +/- to store factory defaults.
Wait 3 seconds to exit setup mode.
- Press the MENU button seven times to set CAM1. Press +/- to select Normal/Mirror mode.
Wait 3 seconds to exit setup mode.
- Press the MENU button eight times to set CAM2. Press +/- to select Normal/Mirror mode.
Wait 3 seconds to exit setup mode.
- Press the MENU button nine times to set Vertical. Press +/- to select Auto/Day/Night.
Wait 3 seconds to exit setup mode.
- Press the MENU button ten times to set Dimmer. Press +/- to select Auto/Day/Night.
Wait 3 seconds to exit setup mode.
- Press the MENU button eleven times to set Scale. Press +/- to select On/Off.
Wait 3 seconds to exit setup mode.
- Press the MENU button twelve times to set Scale Adjustment. Press - to change selected.

NOTES



A CENTURY OF AUTOMOTIVE VISION SAFETY

90-21 144th Place, Jamaica, New York 11435

TEL (800) 227-2095 • FAX (718) 297-0323

techsupport@roscovision.com

www.roscomirrors.com **www.roscovision.com**

RoHS 

Lit. P/N: M11162018